

G4510WA-1/2

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分)

锯弓旋转角度

净重/毛重(千克)

包装尺寸(毫米)

370(0.5HP) 1470X13X0.65 45(50Hz) 54(60Hz) 0°~45° 90° 切割参数(圆形 方形) ●100mm ■100X150mm 45°切割参数(圆形方形)●60mm ■60X100mm 29/31

730X360X450

240pcs

20' 柜装箱数

Model G4510WA-1/2

Motor(W) Blade size(mm) Blade speed(m/min) The bow swivel degree 0°~45° Cutting capacity at 90° •100mm = 100X150mm Cutting capacity at 45° ●60mm ■60X100mm N.W./G.W.(Kgs) Packing size(mm) Unit/20' container

370(0.5HP) 1470X13X0.65 45(50Hz) 54(60Hz) 29/31 730X360X450 240pcs




G4510WA-1 用常规开关 With Standard Switch







G4510WA-2 用手把开关 With Standard Switch



型号 G5015V

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 速度等级 锯弓旋转角度 90°切割参数(圆形方形) 45°切割参数(圆形方形) 60°切割参数(圆形方形) 60°切割参数(圆形方形) 2作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 机器 支腿 550 1735X13X0.65 20-65 无级变速 0°~60° ● 150mm ■ 150X160mm ● 105mm ■ 150X105mm ● 65mm 840 62/65 930X470X480 740X540X330 46pcs

20' 柜装箱数

Model G5015V

Motor(W) 550 Blade size(mm) 1735X13X0.65 Blade speed(m/min) 20 - 65No of speed variable 0°~60° The bow swivel degree Cutting capacity at 90° 150mm 150X160mm 105mm = 150X105mm Cutting capacity at 45° Cutting capacity at 60° • 65mm Working table height(mm) 840 N.W./G.W.(Kgs) 62/65 Packing size(mm) body 930X470X480 740X540X330 stand Unit/20' container 46pcs





型号 G4017

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
电机(瓦)
锯条尺寸(毫米) 锯条速度(米/分)
锯弓旋转角度 90° 切割参数(圆形 方形)
45°切割参数(圆形 方形)
60°切割参数(圆形方形)
工作台高度(毫米) 净重/毛重(千克) 包装尺寸 (毫米) 机器

900(230V) 900/550(380V) 2105X20X0.9 80(230V), 97(110V) 80/40(380V) 0°~60° ● 170mm ■ 140X140mm 210X140mm ● 120mm ■ 110X110mm 130X110mm ●70mm ■ 60X60mm 70X60mm 970 160/200 1260X540X900 750X560X150 28pcs

0

Model G4017

20' 柜装箱数

支腿

Motor(W)	900(23
	900/55
Blade size(mm)	2105X
Blade speed(m/min)	80(230
	80/40(
The bow swivel degree	0°~60°
Cutting capacity at 90°	• 170mn
Cutting capacity at 45°	• 120mn
Cutting capacity at 60°	• 70mm
Table height(mm)	970
N.W./G.W.(Kgs)	160/20
Packing size (mm) body	1260X
stand	750X5
Unit/20' container	28pcs

900(230V) 900/550(380V) 2105X20X0.9 80(230V), 97(110V) 80/40(380V) 0°~60° 170mm = 140X140mm = 210X140mm 120mm = 110X110mm = 130X110mm 70mm = 60X60mm = 70X60mm 970 160/200 1260X540X900 750X560X150









G5018WA 퐨믄

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分)

夹钳旋转角度 90°切割参数(圆形方形) 45° 切割参数(圆形 方形) 工作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 20' 柜装箱数

750W(1HP)

Model G50

Motor(W) Blade size(mm) Blade speed(m/min)

Vice tile Cutting capacity at 90° Cutting capacity at 45° Table height(mm) N.W./G.W.(Kgs) Packing size(mm) Unit/20' container

2360X20	X0.9	3
34, 41,	59,	98(50Hz)
41, 49,	69,	120(60Hz)
0°~45°		11 W
180mm	30	0X180mm
100mm	11	0X170mm
550		
145/175		
1260X46	0X1	080
40pcs		
18\//	٨	
10//	-	

750W(1HP) 2360X20X0.9 34, 41, 59, 98(50Hz) 41, 49, 69, 120(60Hz) 0°~45° 300X180mm 180mm 100mm 110X170mm 550 145/175 1260X460X1080 40pcs

G501

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 夹钳旋转角度 90°切割参数(圆形方形) 45° 切割参数(圆形 方形) 工作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 20' 柜装箱数

刑문

Model Motor(W)

Blade size(mm) Blade speed(m/min) Vice tile Cutting capacity at 90° Cutting capacity at 45° Table height(mm) N.W./G.W.(Kgs) Packing size(mm) Unit/20' container

方形) 方形)	750W(1HP) 2360X20X0.9 34, 41, 59, 98(50Hz) 41, 49, 69, 120(60Hz) 0°~45° 180mm 180X300mm 110mm 110X180mm 550 145/185 1330X460X1080 40pcs
------------	---

750W(1HP) 2360X20X0.9 34, 41, 59, 98(50Hz) 41, 49, 69, 120(60Hz) 0°-45° 180mm 180X300mm 110mm 110X180mm 550 145/185 1330X460X1080 40pcs

G5018WA-G

750W(1HP)

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 夹钳旋转角度 90°切割参数(圆形方形) 45° 切割参数(圆形 方形) 工作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 20' 柜装箱数

刑


2360X20X0.9 36, 50, 62(50Hz) 43, 60, 74(60Hz) 0°~45° 180mm 180X300mm 110X180mm 110mm 550 145/185 1330X460X1080 40pcs

Model G5018WA-L

Motor(W) Blade size(mm) Blade speed(m/min)

Vice tile Cutting capacity at 90° Cutting capacity at 45° Table height(mm) N.W./G.W.(Kgs) Packing size(mm) Unit/20' container

750W(1HP) 2360X20X0.9 36, 50, 62(50Hz) 43, 60, 74(60Hz) 0°~45° 180X300mm 180mm 110mm 110X180mm 550 145/185 1330X460X1080 40pcs



0

1111 Em	0000
坐亏	6002
2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分)

20' 柜装箱数

Motor(W) Blade size(mm)

Model

Blade speed(m/min)

锯弓旋转角度
 90°切割参数(圆形方形)
 45°切割参数(圆形方形)
 ~45°切割参数(圆形方形)
 工作台高度(毫米)
 净重/毛重(千克)
 包装尺寸(毫米)
 机器
 支腿

1100W(1HP) 2360X20X0.9 24, 41, 61, 82(50Hz) 29, 50, 75, 100(60Hz) -45°~+45° 205mm 235X205mm 135mm 135X125mm 160mm 160X205mm 810 190/217 1230X650X820 580X550X260 24pcs G5020 1100W(1HP) 2360X20X0.9 24, 41, 61, 82(50Hz) 29, 50, 75, 100(60Hz)

-45°~+45°

810

190/217

24pcs

1230X650X820 580X550X260

205mm 235X205mm

● 135mm ■ 135X125mm ● 160mm ■ 160X205mm

The bow swivel degree Cutting capacity at 90° Cutting capacity at 45° Cutting capacity at -45° Table height(mm) N.W./G.W.(Kgs) Packing size (mm) body stand

Unit/20' container

G5020G

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分)

刑品

锯弓旋转角度

90° 切割参数(圆形方形) 45° 切割参数(圆形方形) -45° 切割参数(圆形方形) 工作台高度(毫米) 净重/毛重(干克) 包装尺寸(毫米) 机器 支腿

20' 柜装箱数

Model G5020G

Motor(W) Blade size(mm) Blade speed(m/min)

The bow swivel degree Cutting capacity at 90° Cutting capacity at 45° Cutting capacity at -45° Table height(mm) N.W./G.W.(Kgs) Packing size (mm) body stand

Unit/20' container

1100W(1HP) 2360X20X0.9 37, 52, 63(50Hz) 44, 62, 75(60Hz) -45°~+45° ● 205mm ■ 235X205mm ● 135mm ■ 135X125mm ● 160mm ■ 160X205mm

810 190/227 1320X650X820 580X550X260 24pcs

G 1100W(1HP) 2360X20X0.9 37, 52, 63(50Hz) 44, 62, 75(60Hz)) −45°~+45° € 205mm ■ 235X205mm ● 135mm ■ 135X125mm

- 160mm 160X205mm 810
- 190/227 1320X650X820 580X550X260 24pcs

<image>



G5015GC

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 锯弓旋转角度 90° 切割参数(圆形 方形) 45° 切割参数(圆形 方形) 60°切割参数(圆形方形) 工作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 机器 支腿

550 1735X13X0.65 34 0°~60° 150mm 150X160mm 105mm 150X105mm • 65mm 840 62/65 930X470X480 740X540X330

46pcs

20' 柜装箱数

Model G5015GC

Motor(W) Blade size(mm) Blade speed(m/min) The bow swivel degree Cutting capacity at 90° Cutting capacity at 45° Cutting capacity at 60° Working table height(mm) N.W./G.W.(Kgs) Packing size(mm) body stand

550 1735X13X0.65 34 0°~60° 150mm 150X160mm 105mm 150X105mm • 65mm 840 62/65 930X470X480 740X540X330 46pcs

Unit/20' container



G5015B	机器 body			
净重/毛重(千克) N.W./G.W.(Kgs)	58/61			
包装尺寸(毫米) Packing size(mm)	1020X470X520			
锯条速度(米/分) Blade speed(m/min)	26, 32, 51			

G5015G	机器 body
净重/毛重(干克) N.W./G.W.(Kgs)	58/61
包装尺寸(毫米) Packing size(mm)	930X470X48
锯条速度(米/分) Blade speed(m/min)	34

0

er E

G5015BC	机器 body	支腿 stand		
争重/毛重(千克) N.W./G.W.(Kgs)	63/66	38/41		
包装尺寸(毫米) Packing size(mm)	1020X470X520	740X540X330		
据条速度(米/分) Blade speed(m/min)	26, 32, 51			







20' 柜装箱数

28pcs

Model G4023 型 믁 G4023 Motor(W) 电机(瓦) 1100(230V) 1100(230V) 1100/590(380V) 1100/590(380V) 锯条尺寸(毫米) 2450X27X0.9 Blade size(mm) 2450X27X0.9 72(230V), 87(110V) Blade speed(m/min) 锯条速度(米/分) 72(230V), 87(110V) 72/36(380V) 72/36(380V) 锯弓旋转角度 0°~60° The bow swivel degree 0°~60° 90° 切割参数(圆形 方形) ●220mm ■150X150mm Cutting capacity at 90° 220mm ■150X150mm 260X150mm 260X150mm 45°切割参数(圆形 方形) ●150mm ■145X145mm Cutting capacity at 45° ● 150mm ■ 145X145mm 150X145mm 150X145mm 60°切割参数(圆形方形)●90mm Cutting capacity at 60° 85X85mm • 90mm 85X85mm 100X85mm 100X85mm 工作台高度(毫米) 1045 Table height(mm) 1045 N.W./G.W.(Kgs) 净重/毛重(千克) 218/264 218/264 包装尺寸 (毫米)机身 1450X570X1040 Packing size(mm) body 1450X570X1040 支腿 830X780X170 830X780X170 stand

Unit/20' container

28pcs



10["]金属带锯 METAL BAND SAW

型号 G5025

电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 锯弓旋转角度 90°切割参数(圆形方形) 45°切割参数(圆形方形) 60°切割参数(圆形方形) -45°切割参数(圆形方形) -45°切割参数(圆形方形) 工作台高度(毫米) 净重/毛重(干克) 包装尺寸(毫米)机器 支腿

20' 柜装箱数

1500/750(380V) 2715X27X0.9 72/36 -45°~+60° ●250mm ■240X240mm 310X240mm ●200mm ■170X170mm 190X170mm ●120mm ■ 95X95mm 120X95mm ●150mm ■130X130mm 170X90mm 1020 341/394 1540X700X1050 1100X760X180 22pcs

Model G5025

Motor(W) Blade size(mm) Blade speed(m/min) The bow swivel degree Cutting capacity at 90° Cutting capacity at 45° Cutting capacity at 45° Cutting capacity at 60° Cutting capacity at -45° Table height(mm) N.W./G.W.(Kgs) Packing size(mm) body stand Unit/20' container

2715X27X0.9 72/36 -45°~+60° 250mm =240X240mm 310X240mm ●200mm ■170X170mm 190X170mm ●120mm ■ 95X95mm 120X95mm ●150mm ■130X130mm 170X90mm 1020 341/394 1540X700X1050 1100X760X180 22pcs

1500/750(380V)



11["]金属带锯 METAL BAND SAW

型号 G502	27	Model G5027			
电机(瓦) 锯条尺寸(毫米) 锯条速度(米/分) 锯弓旋转角度 90°切割参数(圆形 方形)	1100/2200(380V) 2950X27X0.9 36/72 -45°~+60° ●270mm ■ 260X260mm	Motor(W) Blade size(mm) Blade speed(m/min) The bow swivel degree Cutting capacity at 90°	1100/2200(380V) 2950X27X0.9 36/72 -45°~+60° ●270mm ■ 260X260mm		
45° 切割参数(圆形 方形)	■ 350X240mm •230mm ■ 210X210mm ■ 230X150mm	Cutting capacity at 45°	 350X240mm 230mm = 210X210mm 230X150mm 		
60° 切割参数(圆形 方形) −45° 切割参数(圆形 方形)	●140mm ■ 140X140mm ●200mm ■ 170X170mm ■ 200X140mm	Cutting capacity at 60° Cutting capacity at -45°	●140mm ■ 140X140mm ●200mm ■ 170X170mm ■ 200X140mm		
工作台高度(毫米) 净重/毛重(千克) 包装尺寸(毫米) 机器 支腿 20' 柜装箱数	950 446/551 1770X960X1180 1160X550X210 12pcs	Working table height(mm) N.W./G.W.(Kgs) Packing size(mm) body stand Unit/20' container	950 446/551 1770X960X1180 1160X550X210 12pcs		





G4028

电机(瓦) 2200(380V) 3505X27X0.9 锯条尺寸(毫米) 25, 45, 70 锯条速度(米/分) 工作台尺寸(毫米) 245X245 0°~45° 夹钳旋转角度 90° 切割参数(圆形 方形) ●280mm = 280X300mm 45° 切割参数(圆形 方形) ●195mm ■ 195X280mm 净重/毛重(千克) 650/800 1750X1050X1160 包装尺寸(毫米) 20' 柜装箱数 11pcs

Model G4028

Motor(W) Blade size(mm) Blade speed(m/min) Table size(mm) Vice tilt Cutting capacity at 90° •280mm = 280X300mm N.W./G.W.(Kgs) Packing size(mm) Unit/20' container

2200(380V) 3505X27X0.9 25, 45, 70 245X245 0°~45°

Cutting capacity at 45° •195mm = 195X280mm 650/800 1750X1050X1160 11pcs

METAL BAND SAW



MBS1103 MBS1203	0°		0° 30° 4		5°		60 °	
Ø	170	220	150	190	130	160	70	100
D	170	200	140	180	110	160	60	100
	170x210	260x140	140x140	200x140	110x110	160x140	60x60	120x100

Model:MBS1203

Motor: 230V,50Hz~, 750W 4poles 400V,50Hz,3~, 950/750W, 2/4 poles Reduce gear rate: 18:1 (1~ motor) ; 36:1 (3~ motor) Wheel diameter: 260mm Blade size: 2110x20x0.9mm Blade speed: 65m/min (1~motor) ; 32.5 or 65 m/min(3~ motor) Cutting angle: 0, 30, 45, 60 degree Coolant pump: 230V,45W; Packing size 1150x560x930 Weight : 152/190kg METAL BAND SAW



MBS1103 MBS1203	0°		3	0 °	4	5 °		60 °
Q	170	220	150	190	130	160	70	100
D	170	200	140	180	110	160	60	100
	170x210	260x140	140x140	200x140	110x110	160x140	60x60	120x100

Model:MBS1103

Motor: 230V,50Hz~, 1100W 4poles 400V,50Hz,3~, 1500/1100W, 2/4 poles Reduce gear rate: 18:1 (1~ motor) ; 36:1 (3~ motor) Wheel diameter: 300mm Blade size: 2450x27x0.9mm Blade speed: 75m/min (1~motor) ; 37.5 or 75 m/min(3~ motor) Cutting angle: 0, 30, 45, 60 degree Coolant pump: 230V,45W; Packing size 1350x580x970 Weight : 195/235 kg

Wellcome to: My http://www.dingnuo.com.cn

Factory: Jinan Third CNC Machine Tool Co., Ltd Export : Jinan Haoyuanweiye Trading Co., Ltd

Add:149 Jiqi Road,250022 Jinan,China TEL:86-531- 87960695 FAX:86-531-85663157 SKYPE: yuantaodingnuo Twitter: China machine e-mail:yuantao58@126.com http://sdjichuang.en.alibaba.com http://www.dingnuo.com.cn

> 我公司保留样本内所印各种规格、文字、说明的更改增删权 The descriptions, illustrations and specifications given herein are subject to alteration without notice and thus without any obligation